

Colourbond Base

Double Curved Glass • Tested at ambient temperature of 32°C



2 Tiers





3 Tiers





Model	2 Tiers	CCS 09SB13-2FB	CCS 12SB13-2FB	CCS 15SB13-2FB	CCS 18SB13-2FB	CCS 24SB13-2FB
	3 Tiers	CCS 09SB13-3FB	CCS 12SB13-3FB	CCS 15SB13-3FB	CCS 18SB13-3FB	CCS 24SB13-3FB
Temp. °C (Celcius)	+1 to +6					
Dimension (mm)	900 x 700 x 1350 1200 x 700 x 1350 1500 x 700 x 1350 1800 x 700 x 1350 2400 x 700 x 1350					
Gross Volume (Litres)	316 439 560 682 926					
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz					
Cooling Capacity (W)	646 792 1002 1346 1628					
Wattage (W)	760 - 840 950 - 1050 1045 - 1155 1330 - 1470 1615 - 1785					
Ampere (A)	4.75 - 5.25 5.7 - 6.3 5.7 - 6.3 7.6 - 8.4 9.0 - 10.0					
Refrigerant	R134a R134a R134a R134a R404a					
Defrost System	Forced Air Circulation Forced Air Circulation Forced Air Circulation Forced Air Circulation Forced Air Circulation					
Weight (kg) - 2 / 3 Tiers	144 / 161 190 / 202 236 / 242 282 / 289 328 / 334					
Unit for 20ft / 40ft Container	14 / 30 11 / 24 10 / 22 7 / 16 4 / 8					

2 Tiers



3 Tiers



Back View

Front View

Side View

Optional : To include key lock, prevents unauthorised access to the stores confectioneries