

Stainless Steel Base

Double Curved Glass · Tested at ambient temperature of 32°C





2 Tiers




3 Tiers

Model	2 Tiers	CCS-09SS-2	CCS-12SS-2	CCS-15SS-2	CCS-18SS-2	CCS-24SS-2
	3 Tiers	CCS-09SS-3	CCS-12SS-3	CCS-15SS-3	CCS-18SS-3	CCS-24SS-3
Temp. °C (Celcius)	+1 to +6					
Dimension (mm)	900 x 700 x 1350 1200 x 700 x 1350 1500 x 700 x 1350 1800 x 700 x 1350 2400 x 700 x 1350					
Gross Volume (Litres)	370 499 628 757 1015					
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz					
Cooling Capacity (W)	646 792 1002 1346 1628					
Wattage (W)	450 - 600 600 - 700 700 - 800 1000 - 1400 1500 - 1700					
Ampere (A)	3.0 - 4.0 3.5 - 4.5 4.5 - 5.5 6.0 - 9.0 8.5 - 9.0					
Refrigerant	R134a R134a R134a R134a R404a					
Defrost System	Forced Air Circulation Forced Air Circulation Forced Air Circulation Forced Air Circulation Forced Air Circulation					
Weight (kg) - 2 / 3 Tiers	166 / 173 199 / 208 235 / 246 278 / 290 363 / 380					
Unit for 20ft / 40ft Container	14 / 30 11 / 24 10 / 22 7 / 16 4 / 8					

2 Tiers



3 Tiers



Back View

Front View

Side View

Optional : To include key lock, prevents unauthorised access to the stores confectioneries