

Magnetic Solid Door · Tested at ambient temperature of 38°C



BS 2D/SSCF/Z-N



BS 1D/SSCF4/Z



BS 2D/SSCF6/Z



BS 3D/SSCF8/Z



2 Door

1 Door

2 Door

3 Door

Model	BS 2D/SSCF/Z-N	BS 1D/SSCF4/Z	BS 2D/SSCF6/Z	BS 3D/SSCF8/Z
Temperature °C (Celsius)	+1 to +6	+1 to +6	+1 to +6	+1 to +6
External Dimension (mm)	825 x 760 x 840	1200 x 760 x 840	1800 x 760 x 840	2400 x 760 x 840
Gross Volume (Litres)	131	216	426	634
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz
Cooling Capacity (W)	385	646	792	913
Wattage (W)	346 - 382	361 - 399	475 - 525	570 - 630
Ampere (A)	2.2 - 2.5	2.4 - 2.6	3.3 - 3.7	4.2 - 4.6
Refrigerant	R134a	R404a	R404a	R404a
No. of 1/3 Size Pan (Depth 100mm)		6	8	12
No. of 1/6 Size Pan (Depth 65mm)	4			
No. of 1/9 Size Pan (Depth 65mm)	10			
PVC Coated Shelving	4	2	4	6
Weight (kg)	89	109	143	180
Unit for 20ft / 40ft Container	12 / 26	22 / 46	14 / 28	8 / 16
Top View				
Front View				