

Magnetic Solid Door • Tested at ambient temperature of 38°C



BS 1FDUC/Z/GN



BS 2FDUC/Z/GN



BS 3FDUC/Z/GN



	1 Door	2 Door	3 Door
Model	BS 1FDUC/Z/GN	BS 2FDUC/Z/GN	BS 3FDUC/Z/GN
Temperature °C (Celcius)	+1 to +6	+1 to +6	+1 to +6
External Dimension (mm)	680 x 840 x 2060	1350 x 840 x 2060	2020 x 840 x 2060
Gross Volume (Litres)	552	1197	1853
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz
Cooling Capacity (W)	646	913	1628
Wattage (W)	361 - 399	539 - 596	803 - 887
Ampere (A)	2.4 - 2.6	3.9 - 4.3	5.4 - 6.0
Refrigerant	R134a	R134a	R134a
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
PVC Coated Shelving	5	10	15
Weight (kg)	130	180	250
Unit for 20ft / 40ft Container	20 / 43	10 / 21	6 / 13
Top View			
Front View			

Standard product can be supplied with either Shelving / Food Pan
Castor Wheel / Bullet Fleet