

Magnetic Solid Door • Tested at ambient temperature of 38°C



BS 1FDUF/Z/GN



BS 2FDUF/Z/GN



BS 3FDUF/Z/GN



	1 Door	2 Door	3 Door
Model	BS 1FDUF/Z/GN	BS 2FDUF/Z/GN	BS 3FDUF/Z/GN
Temperature °C (Celcius)	-20 to -14	-20 to -14	-20 to -14
External Dimension (mm)	680 x 840 x 2060	1350 x 840 x 2060	2020 x 840 x 2060
Gross Volume (Litres)	552	1197	1853
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz
Cooling Capacity (W)	772	1112	1526
Wattage (W)	585 - 646	973 - 1075	1364 - 1508
Ampere (A)	2.7 - 3.0	5.1 - 5.6	8.4 - 8.1
Refrigerant	R404a	R404a	R404a
Defrost System	Electric Heater	Electric Heater	Electric Heater
PVC Coated Shelving	5	10	15
Weight (kg)	135	195	260
Unit for 20ft / 40ft Container	20 / 43	10 / 21	6 / 13
Top View			
Front View			

Standard product can be supplied with either
Shelving / Food Pan
Castor Wheel / Bullet Fleet