

Magnetic Solid Door · Tested at ambient temperature of 38°C



BS 1D/PCF4/Z



BS 2D/PCF6/Z



BS 3D/PCF8/Z



	1 Door	2 Door	3 Door
Model	BS 1D/PCF4/Z	BS 2D/PCF6/Z	BS 3D/PCF8/Z
Temperature °C (Celsius)	+1 to +6	+1 to +6	+1 to +6
External Dimension (mm)	1200 x 760 x 1080	1800 x 760 x 1080	2400 x 760 x 1080
Gross Volume (Litres)	216	426	634
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz
Cooling Capacity (W)	415	680	772
Wattage (W)	380 - 420	456 - 504	513 - 567
Ampere (A)	2.6 - 3.0	3.4 - 3.8	3.7 - 4.1
Refrigerant	R404a	R404a	R404a
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
No. of 1/3 Size Pan (Depth 100mm)	6	8	12
PVC Coated Shelving	2	4	6
Weight (kg)	119	156	196
Unit for 20ft / 40ft Container	11 / 23	7 / 14	4 / 8
Top View			
Front View			

Note : 1. Width : 305mm for chopping board
2. Chopping board exclusive