

## Colourbond Base

Double Glass • Tested at ambient temperature of 32°C



2 Tiers





3 Tiers






Model	2 Tiers	RCS 09SB13-2FB	RCS 12SB13-2FB	RCS 15SB13-2FB	RCS 18SB13-2FB	RCS 24SB13-2FB
	3 Tiers	RCS 09SB13-3FB	RCS 12SB13-3FB	RCS 15SB13-3FB	RCS 18SB13-3FB	RCS 24SB13-3FB
Temp. °C (Celcius)	+1 to +6		+1 to +6		+1 to +6	
Dimension (mm)	900 x 700 x 1350		1200 x 700 x 1350		1500 x 700 x 1350	
Gross Volume (Litres)	316		439		560	
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz		230V / 1 / 50Hz 220V / 1 / 60Hz		230V / 1 / 50Hz 220V / 1 / 60Hz	
Cooling Capacity (W)	646		913		1346	
Wattage (W)	706 - 780		892 - 986		977 - 1079	
Ampere (A)	3.7 - 4.1		5.3 - 5.9		6.6 - 7.3	
Refrigerant	R134a		R134a		R134a	
Defrost System	Forced Air Circulation		Forced Air Circulation		Forced Air Circulation	
Weight (kg) - 2 / 3 Tiers	177 / 175		212 / 216		250 / 256	
Unit for 20ft / 40ft Container	14 / 30		11 / 24		10 / 22	

2 Tiers



3 Tiers



Back View

Front View

Side View

Optional : To include key lock, prevents unauthorised access to the stores confectioneries