

Stainless Steel Base

Double Glass • Tested at ambient temperature of 32°C



2 Tiers





3 Tiers





Model	2 Tiers	RCS-09SS-2	RCS-12SS-2	RCS-15SS-2	RCS-18SS-2	RCS-24SS-2
	3 Tiers	RCS-09SS-3	RCS-12SS-3	RCS-15SS-3	RCS-18SS-3	RCS-24SS-3
Temp. °C (Celcius)	+1 to +6					
Dimension (mm)	900 x 700 x 1350 1200 x 700 x 1350 1500 x 700 x 1350 1800 x 700 x 1350 2400 x 700 x 1350					
Gross Volume (Litres)	370 499 628 757 1015					
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 230V / 1 / 50Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz 220V / 1 / 60Hz					
Cooling Capacity (W)	646 913 1002 1346 1628					
Wattage (W)	760 - 840 950 - 1050 1045 - 1155 1330 - 1470 1615 - 1785					
Ampere (A)	4.75 - 5.25 5.7 - 6.3 6.3 - 6.9 7.6 - 8.4 9.0 - 10.0					
Refrigerant	R134a R134a R134a R134a R404a					
Defrost System	Forced Air Circulation Forced Air Circulation Forced Air Circulation Forced Air Circulation Forced Air Circulation					
Weight (kg) - 2 / 3 Tiers	182 / 193 220 / 230 254 / 267 302 / 314 412 / 425					
Unit for 20ft / 40ft Container	14 / 30 11 / 24 10 / 22 7 / 16 4 / 8					

2 Tiers



3 Tiers



Back View

Front View

Side View

Optional : To include key lock, prevents unauthorised access to the stores confectioneries